

PREMIX COMPACT

Thermostatic mixing valve

Ref. 733015

For mixed water 30 - 60°C



DESCRIPTION

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

PREMIX COMPACT thermostatic mixing valve for mixed water distribution from 30 - 60°C:
 For 1 to 11 points-of-use (depending on the flow rate).
 Anti-scalding safety: immediate shut-off if cold water fails.
 Anti-cold shower function - automatic shut-off if hot water supply fails.
 Adjustable temperature from 30 - 60°C, can be blocked by the installer.
 Brass body.
 Filters and non-return valves.
 Recommended flow rate range: from 5 - 33 lpm.
 Thermal shocks are possible.
 M½".
 40mm centres.
 30-year warranty.

ADVANTAGES

-  Automatic shut-off if cold water fails
-  Temperature stability
-  Accessible filters and non-return valves
-  Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

| | |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector | M½" |
| Technology | Thermostatic |
| Length | 120mm |
| Finish | Nickel-plated |
| Norms |     |
| Warranty |  |
| Repairability |  |

