

# PREMIX COMPACT

## Thermostatic mixing valve

Ref. 733020

For mixed water 30 - 60°C



### DESCRIPTION

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733020**

Thermostatic mixing valve for mixed water distribution from 30 - 60°C:  
For 1 to 11 sanitary points-of-use (depending on the flow rate).  
Anti-scalding safety: immediate shut-off if cold water supply fails.  
Cold shower failsafe: automatic shut-off if hot water supply fails.  
Adjustable temperature from 30 - 60°C, can be blocked by the installer.  
Brass body.  
Filters and non-return valves.  
Minimum flow rate to operate: from 5 - 33 lpm.  
Thermal shocks are possible.  
M $\frac{3}{4}$ ".  
40mm centres.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733020**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M $\frac{3}{4}$ "                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Technology    | Thermostatic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Length        | 120mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Finish        | Nickel-plated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Norms         |       |
| Warranty      |                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Repairability |                                                                                                                                                                                                                                                                                                                                                                                                                                      |

### ADVANTAGES



Automatic flow reduction if cold/hot water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

