TEMPOFLUX 2 direct flush valve

Ref. 762902

Time flow direct flush WC valve

DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762902

Flush system without cistern: directly connected to pipework.
Chrome-plated metal wall plate Ø 195mm.
Concealed mechanical fixing of the wall plate.
Multipurpose recessing housing.
Recessing depth can be adjusted from 0 - 20mm.
3L/6L dual flush, can be adjusted to 2L/4L.
Soft-touch operation.
Vacuum breaker.
Integrated stopcock and flow rate / flush volume adjuster.
Solid brass body.
Chrome-plated metal push-button.
In-line inlet M¾".
Outlet connection for PVC tube Ø 26/32mm.
Acoustic level complies with European standard EN 12541 class II.
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
Base flow rate: 1L/sec at 1 bar dynamic pressure.
Compatible with rain water.
Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
30-year warranty.
This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

ADVANTAGES

- Soft-touch operation
- Dual flush 3L/6L
- No cistern: no stagnant water
- Recessed installation

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762902

Connector	3/4"
Technology	Time flow
Flow rate	3L/6L
Finish	Chrome-plated metal
Norms	
Warranty