

TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve



DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762150

Flush system without cistern: directly connected to pipework.

For walls \leq 140mm.

3L/6L dual flush can be adjusted to 2L/4L.

Soft-touch operation.

Vacuum breaker.

Integrated stopcock and flow rate / flush volume adjuster.

Solid brass body.

Chrome-plated metal push-button.

In-line inlet M $\frac{3}{4}$ ".

Outlet connection for PVC tube \varnothing 26/32mm.

Threaded rod can be cut to size.

Acoustic level complies with European standard EN 12541 class II.

Base flow rate: 1 L/sec at 1 bar dynamic pressure.

Compatible with rain water.




Suitable for rimless WC pans without flow rate regulation.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762150

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	 
Warranty	

ADVANTAGES



Soft-touch operation



Dual flush 3L/6L



No cistern: no stagnant water



Cross wall installation

