TEMPOFLUX 1 direct flush valve

Ref. 761900

Direct flush WC valve

DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761900

Flush system without cistern: directly connected to pipework.
Chrome-plated brass wall plate Ø 195mm.
Multipurpose recessing housing.
Soft-touch operation.
Time flow ~7 seconds.
Vacuum breaker.
Integrated stopcock and flow/volume rate adjuster.
Solid brass body and chrome-plated push-button.
In-line inlet M¾".
Outlet connection for PVC tube Ø 25mm.
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
Base flow rate: 1L/sec at 1 bar dynamic pressure.
30-year warranty.
This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

ADVANTAGES

- No cistern: no stagnant water
- Wall recessed installation
- Powerful flush and immediately available
- Direct flush reduces the risk of leaks

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761900

Connector	¾"
Norms	
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY