

## TEMPOFLUX 1 direct flush kit

Ref. 761003

Time flow direct flush WC valve

### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761003

Flush system without cistern: directly connected to pipework.  
For wall-mounted exposed installation.  
Soft-touch operation.  
Time flow ~7 seconds.  
Vacuum breaker.  
Integrated stopcock and flow rate / flush volume rate adjuster.  
Chrome-plated solid brass body and push-button.  
Angled inlet M $\frac{3}{4}$ ".  
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
With stainless steel flush tube, collar and connection washer.  
Compatible with rain water.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761003

|           |                                                                                     |
|-----------|-------------------------------------------------------------------------------------|
| Connector | $\frac{3}{4}$ "                                                                     |
| Height    | 565mm                                                                               |
| Length    | 215mm                                                                               |
| Norms     |  |
| Warranty  |  |



### ADVANTAGES



No cistern: no stagnant water



Chrome-plated solid brass



Powerful flush and immediately available



Direct flush reduces the risk of leaks

