

## TEMPOFLUX 1 direct flush kit

Ref. 761025

Time flow direct flush WC system

### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761025

Flush system without cistern: directly connected to pipework.  
For wall-mounted exposed installation.  
Soft-touch operation.  
Time flow ~7 seconds.  
Vacuum breaker.  
Chrome-plated solid brass body and push-button.  
Angled inlet M $\frac{3}{4}$ ".  
With flush tube Ø 25mm and Ø 24mm (replacements for SCHELL & BINE 120000 models).  
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
Compatible with rain water.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761025

|           |                                                                                                                                                                         |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector | $\frac{3}{4}$ "                                                                                                                                                         |
| Norms     |   |
| Warranty  |                                                                                      |



### ADVANTAGES



No cistern: no stagnant water



Chrome-plated solid brass



Powerful flush and immediately available



Direct flush reduces the risk of leaks

