Wall-mounted twin hole mixer - 60 lpm

Ref. 5645T2

Swivelling under spout L. 200mm



DESCRIPTION

Wall-mounted twin hole mixer - 60 lpm - Ref. 5645T2

Wall-mounted twin hole mixer with swivelling, tubular under spout Ø 22mm L. 200mm with star-shaped brass flow straightener.
Water-free, guided valve heads with reinforced mechanisms.
Shock-resistant, ergonomic ball levers.
Flow rate 60 lpm at 3 bar achieved within 90°.
Full flow rate 90 lpm at 3 bar.
Spout with smooth interior.
One-piece body and spout made from chrome-plated brass.
M1/2" M3/4" offset connectors supplied with escutcheons.
Suitable for disposal sinks.
30-year warranty.

ADVANTAGES

- Flow rate 60 lpm within first 90°
- One-piece body and spout in chrome-plated brass
- Helps create clear work surfaces

TECHNICAL CHARACTERISTICS

Wall-mounted twin hole mixer - 60 lpm - Ref. 5645T2

Connector	M1/2"
Spout length	200mm
Flow rate	60 lpm
Width to the wall	57mm
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY



