Wall-mounted eye wash station

Ref. 9102

With manual control

DESCRIPTION

Wall-mounted eye wash station - Ref. 9102

Wall-mounted eye wash station with manual control equipped with:
304 stainless steel basin Ø 250mm, green powder-coated finish.
Two spray heads fitted with protective caps in shock-resistant green ABS; will eject automatically when activated.
1/4-turn, nickel-plated brass valve opens and closes quickly.
30-year warranty.
Operation:
Water flow is activated by the hand control. The eye wash will continue to operate when the hand control is released. To stop the flow, pull the hand control in the opposite direction.
Flow rate 20 lpm at 3 bar dynamic pressure.
Aerators with stainless steel double filters.
Water supply M1/2".
Pipework made from galvanised steel, grey powder-coated finish.
Hand control made from galvanised steel, green powder-coated finish.
Wall-mounted on a brass plate (screws not included.)
Supplied with identification sign for first aid equipment: "Eye Wash".

ADVANTAGES

- Gentle spray, quick and easy to activate
- Maintenance without removing the equipment
- Rapid flow rates for decontamination

TECHNICAL CHARACTERISTICS

Wall-mounted eye wash station - Ref. 9102

Supply	M1/2"
Height	195mm
Flow rate	20 lpm at 3 bar dynamic pressure
Width to the wall	250mm
Finish	Epoxy
Norms	
Warranty	
Repairability