TEMPOMATIC MIX 4 electronic mixer

Ref. 490006

Integrated batteries, stopcocks



ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush



Deck-mounted electronic basin mixer:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after the last use).

Active infrared presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexibles F3/8" with stopcocks, filters and non-return valves.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

DESCRIPTION

Side temperature control with adjustable maximum temperature limiter.


Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490006

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS WWRAS
Warranty	30 g



© DELABIE https://www.delabie.com