## Mechanical mixer for sinks or troughs

Ref. 2510T

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm



Deck-mounted mechanical sink mixer.

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

 $\emptyset$  40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.


30-year warranty.

## Pre-set maximum temperature limiter Body and spout with smooth interiors. Body and spout made from chrome-plated brass. Flow rate limited to 9 lpm at 3 bar. Ergonomic: solid lever is easy to grip Solid control lever. Supplied with PEX flexibles F3/8". Fixing reinforced by 2 stainless steel rods. Comfort: optimum drop height and

## TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2510T

Connector	F3/8"
Height	177mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 😥 🗓
Warranty	30 S WARRANTY
Repairability	50 g



Hygiene: smooth interior reduces

bacteria

spout projection

© DELABIE https://www.delabie.com