

# Mechanical mixer for sinks or troughs

Ref. 2510T

Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm





## DESCRIPTION

**Mechanical mixer for sinks or troughs - Ref. 2510T**

Deck-mounted mechanical sink mixer.  
Single hole mechanical mixer with swivelling spout H. 155mm L. 230mm fitted with hygienic flow straightener.  
Spout suitable for fitting a BIOFIL point-of-use filter.  
Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.  
Body and spout with smooth interiors.  
Body and spout made from chrome-plated brass.  
Flow rate limited to 9 lpm at 3 bar.  
Solid control lever.  
Supplied with PEX flexibles F3/8".  
Fixing reinforced by 2 stainless steel rods.  
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Single hole mixer suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical mixer for sinks or troughs - Ref. 2510T**

Connector	F3/8"
Height	177mm
Drop height	155mm
Spout length	230mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	
Repairability	



## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Ergonomic: solid lever is easy to grip



Comfort: optimum drop height and spout projection

