

# Wall-mounted pre-rinse set with mixer

Ref. 5636

Without bib tap

## DESCRIPTION

Wall-mounted pre-rinse set with mixer - Ref. 5636

Complete pre-rinse set without bib tap suitable for intensive use in professional kitchens.

Wall-mounted mixer, F3/4" with adjustable centres with:

- valve heads with reinforced mechanisms and ergonomic controls.

- M1/2" M3/4" offset connectors.

- non-return valves integrated in the mixer.

Black hand spray with adjustable jet and 9 lpm flow rate at the outlet (ref. 433010).

Scale-resistant hand spray with shock-resistant tip.

Black, reinforced, food-grade flexible hose L. 0.95m.

3/4" stainless steel column.

Adjustable wall bracket.

Stainless steel spring guide.

Pre-rinse set.

30-year warranty.

## TECHNICAL CHARACTERISTICS

Wall-mounted pre-rinse set with mixer - Ref. 5636

|                   |                                                                                                                                                                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector         | M1/2"                                                                                                                                                                                                                                                                                                                                           |
| Height            | 860 - 930mm                                                                                                                                                                                                                                                                                                                                     |
| Drop height       | 235 - 305mm                                                                                                                                                                                                                                                                                                                                     |
| Flow rate         | 9 lpm via the hand spray                                                                                                                                                                                                                                                                                                                        |
| Width to the wall | 35 - 162mm                                                                                                                                                                                                                                                                                                                                      |
| Finish            | Stainless steel                                                                                                                                                                                                                                                                                                                                 |
| Norms             |     |
| Warranty          |                                                                                                                                                                                                                                                              |
| Repairability     |                                                                                                                                                                                                                                                              |



## ADVANTAGES



Anti-torsion rotating nuts and PVC sheath



Comfort: ergonomic controls



Hygiene: PVC flexible, scale-resistant spray



Increased resistance: high quality flexible

