DELABIE

Auto-draining shower kit with thermostatic mixer

Ref. H9630SHYG

Thermostatic sequential mixer with no non-return valves

DESCRIPTION

Auto-draining shower kit with thermostatic mixer - Ref. H9630SHYG

SECURITHERM thermostatic sequential shower kit with auto-draining device. • Mixer with scale-resistant, thermostatic sequential cartridge:

Thermostatic sequential mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior and low water volume.

Flow rate regulated at 9 lpm.

Chrome plated brass body and Hygiene lever L. 100mm.

M1/2" bottom shower outlet.

Wall-mounted mixer with 2 standard offset M1/2" M3/4" connectors.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

• Shower head (ref. 813) with flexible shower hose (ref. 836T3) and

adjustable, chrome-plated wall-mounted support (ref. 845).

• Auto-draining device FM1/2" for installation between the flexible hose and the shower head, automatically drains the shower head and flexible hose (reduces bacterial development) (ref. 880). Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with thermostatic mixer - Ref. H9630SHYG

Connector	M1/2"
Technology	SECURITHERM single control thermostatic mixer, Securitouch
Depth	175mm
Length	184mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass

Norms





ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability



DELABIE

Warranty	VIABRANTY
Repairability	500 REALINABILITY