

# SECURITHERM shower panel

Ref. 792305

Thermostatic time flow

## DESCRIPTION

**SECURITHERM shower panel - Ref. 792305**

Thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet via in-line stopcocks M1/2".  
SECURITHERM thermostatic mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Time flow ~30 seconds.  
Flow rate set at 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
With soap dish.  
Concealed fixings.  
Filters and non-return valves.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792305**

|                     |                                                                                                                                                                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                                                                                                                                                                                                       |
| Technology          | Time flow                                                                                                                                                                                                                                                   |
| Height              | 1050mm                                                                                                                                                                                                                                                      |
| Depth               | 65mm                                                                                                                                                                                                                                                        |
| Width               | 210mm                                                                                                                                                                                                                                                       |
| Flow rate           | 6 lpm                                                                                                                                                                                                                                                       |
| Temperature limiter | Thermostatic                                                                                                                                                                                                                                                |
| Finish              | Aluminium                                                                                                                                                                                                                                                   |
| Norms               |    |
| Warranty            |                                                                                                                                                                          |



## ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



80% water savings



Aluminium panel, brass controls

