

TEMPOMATIC electronic shower kit

Ref. 452159

Electronic



DESCRIPTION

TEMPOMATIC electronic shower kit - Ref. 452159

Cross wall electronic shower kit:
TEMPOMATIC electronic valve for mixed water supply.
For walls $\leq 155\text{mm}$.
Power supply by electronic unit with solenoid valve 1/2".
230/12V transformer.
2 operation modes:
- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor $\sim 10\text{ cm}$.
Duty flush (~ 60 seconds every 24 hours after the last use).
Adjustable time flow from 30 to 60 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Chrome-plated solid brass.
Wall plate flush to the wall.
Threaded rods can be cut-to-size.
Electronic shower kit suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	  
Warranty	

ADVANTAGES



230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes

