TEMPOMATIC electronic shower kit

Ref. 452159

Electronic



Cross wall electronic shower kit:

TEMPOMATIC electronic valve for mixed water supply.

TEMPOMATIC electronic shower kit - Ref. 452159

For walls ≤ 155mm.

Power supply by electronic unit with solenoid valve 1/2".

230/12V transformer.

2 operation modes:

- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor ~10 cm. Duty flush (~60 seconds every 24 hours after the last use).

Adjustable time flow from 30 to 60 seconds.

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Chrome-plated solid brass.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

Electronic shower kit suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	ACS (E
Warranty	30g WARRANTY





230/12V




Total hygiene: no manual contact




Anti-bacterial duty flush



2 operation modes





© DELABIE https://www.delabie.com