TEMPOMATIC electronic shower kit

Ref. 452159

Electronic



DESCRIPTION

TEMPOMATIC electronic shower kit - Ref. 452159

Cross wall electronic shower kit:

TEMPOMATIC electronic valve for mixed water supply.

For walls ≤ 155mm.

Power supply by electronic unit with solenoid valve 1/2".

230/12V transformer.

2 operation modes:

- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor \sim 10 cm. Duty flush (\sim 60 seconds every 24 hours after the last use).

Adjustable time flow from 30 to 60 seconds.

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Chrome-plated solid brass.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

Electronic shower kit suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	ACS (E
Warranty	30 g



