

# TEMPOGENOU time flow tap

Ref. 735400

Knee-operated



## DESCRIPTION

TEMPOGENOU time flow tap - Ref. 735400

Knee-operated time flow basin valve:  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Reinforced control lever.  
Brass wall plate with reinforced fixing via 4 stainless steel screws.  
Cold or mixed water supply.  
Chrome-plated brass body M $\frac{1}{2}$ ".  
Straight model for in-line.  
30-year warranty.

## ADVANTAGES



85% water savings



Knee-operated



Reinforced fixing and rod



Total hygiene: no manual contact

## TECHNICAL CHARACTERISTICS

TEMPOGENOU time flow tap - Ref. 735400

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M $\frac{1}{2}$ "                                                                                                                                                                                                                                                                                                                               |
| Technology    | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Length        | 435mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

