SECURITHERM dual control shower panel

Ref. 792344

Thermostatic and mechanical dual control



SECURITHERM dual control shower panel - Ref. 792344

Dual control thermostatic shower panel with handset:

Large model satin stainless steel shower panel for wall-mounted, exposed installation.

Top inlet via in-line stopcocks M½".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.

Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.

Non-time flow valves control fixed ROUND shower head and handset with flexible.

Thermal shocks are possible.

Concealed fixings.

Filters and non-return valves.

Shower panel suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792344

Connector	M½"
Technology	Non-time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS STF 🐵 🗓
Warranty	30 gg WARRANTY



ADVANTAGES



Thermostatic temperature regulation




Instant shut-off if cold water fails



Fixed shower head or handset



Aluminium panel, brass controls



© DELABIE https://www.delabie.com