

TEMPOMIX time flow shower mixer

Ref. 790925

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790925

Recessed time flow shower kit:
 Chrome-plated Ø 195mm wall plate.
 Standard recessing housing.
 Recessing depth adjustable from 28 - 43mm.
 TEMPOMIX ¼" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 12 lpm at 3 bar.
 M½" connectors for Ø 15mm copper tubes.
 Integrated non-return valves and filters.
 Chrome-plated metal control.
 30-year warranty.
 As this model does not come with waterproof recessing housing the installer must ensure the watertightness of the recessing area and allow for run-off of leaks and condensation (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790925

Connector	M1/2" Ø 15mm
Technology	Time flow
Flow rate	12 lpm
Norms	   
Warranty	

ADVANTAGES



Recessed wall installation



Time flow system tested to 500,000+ operations



Soft-touch operation

