

# TEMPOMIX time flow shower mixer

Ref. 790425

Single control time flow






## DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790425

Recessed time flow shower kit:  
 Stainless steel wall plate 160 x 160mm.  
 Standard recessing housing.  
 Recessing depth adjustable from 28 - 48mm.  
 TEMPOMIX ¾" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds, soft-touch operation.  
 Flow rate 12 lpm at 3 bar.  
 M½" connections for Ø 15mm copper tubes.  
 Integrated non-return valves and filters.  
 Chrome-plated metal push-button.  
 30-year warranty.  
 As this model does not come with waterproof recessing housing the installer must ensure the watertightness of the recessing area and allow for run off of leaks and condensation. (see installation guide).

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790425

Connector	M½" Ø 15mm
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	12 lpm
Norms	ACS  
Warranty	

## ADVANTAGES



Recessed wall installation



Time flow system tested to over 500,000 operations



Soft-touch operation

