DELABIE

SECURITHERM EP pressurebalancing shower mixer

Ref. 2739TEPS

Wall-mounted single control mixer, solid lever



DESCRIPTION

SECURITHERM EP pressure-balancing shower mixer - Ref. 2739TEPS

Wall-mounted single control mechanical shower mixer. Wall-mounted single control mixer with Securitouch thermal insulation to prevent burns.

 \varnothing 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa). Constant temperature regardless of pressure or flow rate variations in the system.

Body with smooth interior and low water volume.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and solid control lever.

M1/2" shower outlet with integrated non-return valve.

Mixer with offset standard wall connectors, M1/2" M3/4".

Filters and non-return valves on the inlets.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement homes, hospitals and clinics.

Shower mixer suitable for people with reduced mobility. Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing shower mixer - Ref. 2739TEPS

Connector	M1/2"
Technology	SECURITHERM EP mechanical mixer
Width	182mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	
Warranty	30 ES WARBANTY
Repairability	REPARABILITY

ADVANTAGES



HW flow rate reduced if CW fails

Pressure-balancing: reduces temperature variations



Hygiene: smooth interior reduces bacteria



Maximum hygiene: low water volume

