SECURITHERM BIOCLIP thermostatic basin mixer

Ref. H96051

Single hole, sequential thermostatic mixer H. 95mm L. 120mm



ADVANTAGES



Maximum hygiene: mixer with no non-return valves



Hygiene: can be removed for internal cleaning



SECURITHERM: Optimal antiscalding safety



Sequential: opens/closes with cold water

DESCRIPTION

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H96051

Deck-mounted thermostatic SECURITHERM basin mixer.

Sequential thermostatic mixer: opens and closes with cold water.

No risk cross flow between the cold and hot water.

No non-return valves on the inlets.

BIOCLIP: mixer is easy to remove for cleaning and disinfection.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns.

Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic flow straightener with no impurity retention and thermal shock-resistant.

Scale-resistant sequential thermostatic cartridge for single control of flow rate and temperature.

Temperature adjusts from cold water up to 40°C with temperature limiter set at 40°C .

Thermal and chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate limited to 5 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 146mm.

No pop-up waste.

F3/8" PEX flexibles.

Fixing reinforced by 2 stainless steel rods.

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.


30-year warranty.

Also available with copper tails.

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H96051

Connector	F3/8"
Technology	SECURITHERM BIOCLIP sequential Securitouch
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS DVGW



DELABIE

Warranty	30 gg WASTANTY
Repairability	50 g

© DELABIE https://www.delabie.com