

# TEMPOMIX 3 time flow mixer

Ref. 794370

Soft-touch operation



## DESCRIPTION

**TEMPOMIX 3 time flow mixer - Ref. 794370**

Wall-mounted single control time flow basin mixer:  
Soft-touch operation.  
Temperature adjustment and operation via the push-button.  
Time flow pre-set at ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 - 6 lpm.  
Scale-resistant flow straightener.  
Chrome-plated metal body M $\frac{1}{2}$ ".  
Fixed spout.  
Filters and non-return valves.  
Adjustable maximum temperature limiter.  
M $\frac{1}{2}$ " offset connectors for centres from 130 - 170mm.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow mixer - Ref. 794370**

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M1/2"                                                                                                                                                                                                                                                                                                                                           |
| Technology    | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Width         | 150mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

## ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Sleek and slim design

