

TEMPOMIX 3 time flow shower mixer

Ref. 794470

Time flow single control



DESCRIPTION

TEMPOMIX 3 time flow shower mixer - Ref. 794470

Exposed time flow shower mixer:
TEMPOMIX 3 single control mixer, bottom outlet, M $\frac{1}{2}$ " inlet with M $\frac{3}{4}$ " connector.

Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).

For wall-mounted, exposed installation.

Soft-touch operation.

Time flow pre-set at ~30 seconds.

Flow rate 6 lpm at 3 bar, can be adjusted from 6 lpm - 12 lpm.

Chrome-plated brass.

Integrated filters and non-return valves.

Chrome-plated metal push-button.




M $\frac{1}{2}$ " offset connectors for 130 - 170mm centres.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower mixer - Ref. 794470

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Width	150mm
Flow rate	9 lpm
Norms	ACS  
Warranty	

ADVANTAGES



Soft-touch operation



Time flow system tested to over 500,000 operations

