SECURITHERM EP BIOCLIP pressure-balancing basin mixer

Ref. 28211LEP

Single hole removable BIOCLIP mixer H.95 L.120, Hygiene lever

DESCRIPTION

SECURITHERM EP BIOCLIP pressure-balancing basin mixer - Ref. 28211LEP

Deck-mounted mechanical basin mixer with pressure-balancing.
BIOCLIP mechanical mixer: mixer can be removed entirely for cleaning and disinfection.
Single hole mixer with spout H. 95mm L. 120mm fitted with a BIOSAFE hygienic flow straightener.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.
Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Stable temperature regardless of variations in pressure and flow rate in the system.
Body and spout with smooth interiors and low water volume.
Flow rate limited to 5 lpm at 3 bar.
Hygiene control lever L. 150mm.
No pop-up waste.
F3/8" PEX flexibles.
Filters and non-return valves.
Fixing reinforced via 2 stainless steel rods.
Mechanical mixer with SECURITHERM pressure-balancing, ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- Hygiene: remove for internal descaling
- Hygiene: smooth interior reduces bacteria
- EP: reduces temperature variations

TECHNICAL CHARACTERISTICS

SECURITHERM EP BIOCLIP pressure-balancing basin mixer - Ref. 28211LEP

Connector	F3/8"
Technology	SECURITHERM EP BIOCLIP
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass



Norms	ACS BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY