

SECURITHERM EP pressure-balancing basin mixer

Ref. 2446EP

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EP

Wall-mounted SECURITHERM pressure balancing (EP) basin mixer.
Wall-mounted mixer with flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Securitouch thermal insulation prevents burns.

Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interior and low water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Sculptured control lever.

Mixer supplied with offset STOP/CHECK connectors M1/2" M3/4" ideal for use in hospitals.

Recommended installation height: 110 - 200mm above the basin surface.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EP

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms



Warranty



ADVANTAGES



EP: HW flow reduces if CW supply fails




Securitouch thermal insulation prevents burns



EP: prevention of pressure variations



Hygiene: smooth interior reduces bacteria



Repairability

