

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741TP

Dual control mixer with thermal insulation






DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP




- Dual control SECURITHERM thermostatic shower mixer with:
- Anti-scalding safety: shuts off automatically if cold or hot water fails (and vice versa).
 - Securitouch thermal insulation to prevent burns.
 - Scale-resistant thermostatic cartridge for temperature adjustment.
 - 1/4-turn ceramic head for flow rate adjustment.
 - Adjustable temperature from 25°C to 41°C.
 - Maximum temperature limiter pre-set to 38°C.
 - Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.
 - Flow rate regulated at 9 lpm.
 - Chrome-plated brass body and ERGO controls.
 - M1/2" shower outlet.
 - Filters and non-return valves built-in to inlets F3/4".
- Mixer with in-line STOP/PURGE connectors M1/2" M3/4" ideal for hospitals.
10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP

Connector	M1/2"
Technology	SECURITHERM Securitouch
Depth	95mm
Length	286mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Norms	 
Warranty	

ADVANTAGES

-  SECURITHERM: Anti-scalding safety
-  Securitouch thermal insulation prevents burns
-  Thermostatic: complete temperature stability
-  Pre-set maximum temperature limiter

