

TEMPOMIX 3 time flow mixer

Ref. 79400015

Soft-touch operation, Ø 15mm stopcocks



DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 79400015

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow pre-set at ~7 seconds, adjustable from 6 to 9 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated solid brass body.
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.
Fixing reinforced by 2 stainless steel rods.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 79400015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	
Warranty	

ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Chrome-plated solid brass, reinforced fixings



Sleek design

