DELABIE

SECURITHERM thermostatic basin mixer

Ref. H9600610

Single hole thermostatic sequential mixer, H. 95mm L. 120mm

DESCRIPTION

SECURITHERM thermostatic basin mixer - Ref. H9600610

Deck-mounted SECURITHERM thermostatic basin mixer.

Thermostatic sequential mixer: opens and closes with cold water. No risk of cross flow between hot and cold water.

No non-return valve on the inlets.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns.

Single hole mixer with straight spout H. 95mm L. 120mm fitted with a hygienic flow straightener for no impurity retention and resistance to thermal shocks. Scale-resistant thermostatic sequential cartridge for single control of flow rate and temperature.

Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C.

Tested without water to comply with NHS requirements. No pre-set temperature.

Thermal and chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate limited to 5 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 146mm. No pop-up waste.

Supplied with copper tails and stopcocks in chrome-plated brass.

Fixing reinforced by 2 stainless steel rods.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

30-year warranty.

Also available with PEX flexibles.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - Ref. H9600610

Connector	M1/2'' Ø 15mm
Technology	SECURITHERM Securitouch sequential mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass



ADVANTAGES



Sequential: opens/closes with cold water




Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Securitouch: thermal insulation prevents burns



DELABIE

Norms	
Warranty	30 Store
Repairability	REALIVABILITY