

TEMPOMATIC 4 electronic tap

Ref. 44000015

Recessed mains supply, 15mm stopcock



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000015

Deck-mounted electronic basin tap:
 230/6V recessed mains supply.
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 sec. every 24h after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body.
 Cap fixed in place by two concealed screws.
 PEX flexible with stopcock, filter and Ø 15mm conical inlet.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000015

| | |
|--------------|---|
| Supply | 230/6V (recessed mains supply) |
| Connector | M1½" Ø 15mm |
| Technology | Electronic |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms |  |
| Warranty |  |

ADVANTAGES

-  Proven water savings: 90%
-  Hygiene: no manual contact
-  Recessed mains supply
-  Integrated solenoid valve

