

# BINOPTIC electronic tap

Ref. 47801515

Battery-operated, Ø 15mm compression fittings



## DESCRIPTION

**BINOPTIC electronic tap - Ref. 47801515**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
123 6V Lithium battery.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared movement detection, sensor at the end of the spout optimises detection.  
Chrome-plated solid brass body.  
PEX flexible with filter, solenoid valve and Ø 15mm compression fittings.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with a smooth interior and low volume of water (limits bacterial niches).  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 47801515**

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Supply       | 6V battery                                                                          |
| Connector    | M1/2" Ø 15mm                                                                        |
| Technology   | Electronic                                                                          |
| Drop height  | 90mm                                                                                |
| Spout length | 125mm                                                                               |
| Flow rate    | 3 lpm                                                                               |
| Warranty     |  |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

