

## BINOPTIC electronic tap

Ref. 379D1315

Mains supply, Ø 15mm conical inlet



### DESCRIPTION

**BINOPTIC electronic tap - Ref. 379D1315**

Cross wall electronic basin tap:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared movement detection, sensor at the end of the spout optimises detection.  
Filter, solenoid valve and Ø 15mm conical inlet.  
Chrome-plated solid brass body.  
Chrome-plated spout L. 135mm for cross wall installation ≤ 190mm.  
Sensor cable, flexibles and mounting all pass through the same hole.  
Anti-blocking security.  
Spout with a smooth interior and low water volume (limits bacterial niches).  
30-year warranty.

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact





LED diagnostic aid



Duty flush limits bacterial proliferation

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 379D1315**

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Spout length	135mm
Flow rate	3 lpm
Norms	 
Warranty	