

TEMPOMATIC MIX 2

electronic mixer

Ref. 49400015

Mains supply, Ø 15mm conical inlets



DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400015

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body.
PEX flexibles with filters and solenoid valves Ø 15mm for compression fittings.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with adjustable maximum temperature limiter.
Solenoid valves are upstream of the mixing chamber.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400015

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

