

TEMPOMATIC Electronic tap

Ref. 44115715

Mains supply, conical inlet Ø 15mm



DESCRIPTION

TEMPOMATIC Electronic tap - Ref. 44115715

Cross wall electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shockproof infrared presence detection sensor for wall ≤ 165mm.
Anti-blocking security.
Solenoid valve with filter and Ø 15mm conical inlet.
Chrome-plated fixed spout L. 170mm for wall ≤ 165mm with anti-rotating pin.
Threaded rods can be cut to size.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC Electronic tap - Ref. 44115715

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Depth	165mm
Spout length	170mm
Flow rate	3 lpm
Norms	CE
Warranty	30 YEARS WARRANTY

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Duty flush limits bacterial proliferation

