

# TEMPOSOFT MIX 2 time flow mixer

Ref. 74250015

Soft-touch operation, Ø 15mm stopcocks




## DESCRIPTION

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015

Deck-mounted time flow basin mixer:  
Soft-touch operation.  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated solid brass body.  
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.  
Fixing reinforced by 2 stainless steel rods.  
Side temperature control with standard lever and maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	85mm
Spout length	100mm
Flow rate	3 lpm
Norms	
Warranty	
Repairability	



## ADVANTAGES



Exceptional water savings: 85%



Chrome-plated solid brass body



Soft-touch operation



Sleek design

