

# SECURITHERM shower panel

Ref. 79230015

Thermostatic time flow

## DESCRIPTION

**SECURITHERM shower panel - Ref. 79230015**

Time flow thermostatic shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
Top inlet via in-line stopcocks and conical Ø 15mm inlets.  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C  
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
Time flow shower valve ~30 seconds.  
Flow rate 6 lpm at 3 bar.  
Concealed fixings.  
Filters and non-return valves.  
Time flow shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 79230015**

Connector	M½" Ø 15mm
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	<b>ACS</b>
Warranty	<b>30</b> YEAR WARRANTY



## ADVANTAGES



Thermostatic control



Instant shut-off if cold water supply fails



80% water savings



Aluminium body, brass controls

