

# Sequential thermostatic shower mixer

Ref. H963015

SECURITHERM mixer with no non-return valve, bottom outlet



## DESCRIPTION

Sequential thermostatic shower mixer - Ref. H963015

SECURITHERM thermostatic sequential shower mixer.

Thermostatic sequential mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.

Prevents cold showers: shuts off immediately if hot water supply fails

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.

Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior (reduces niches where bacteria can develop).

Flow rate regulated at 9 lpm.

Chrome-plated brass body and Hygiene control lever L. 100mm.

M1/2" bottom shower outlet.

Wall-mounted mixer with M1/2" M3/4" inline STOP/CHECK.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H963015

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | SECURITHERM Securitouch sequential thermostatic mixer |
| Length              | 184mm   |
| Flow rate           | 9 lpm   |
| Temperature limiter | Yes   |
| Finish              | Chrome-plated brass                                   |
| Norms               |   |
| Warranty            |   |
| Repairability       |   |

## ADVANTAGES



Sequential, opens/closes with cold water



No non-return valves on the inlets



SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability

