TEMPOMATIC tap with BIOCLIP spout

Ref. 20804T2

Electronic wall-mounted tap with stainless steel spout





DESCRIPTION

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Wall-mounted electronic basin tap for mounting on panels.

Electronic tap with BIOCLIP removable spout

Infrared tap supplied with 2 removable BIOCLIP stainless steel spouts L. 77mm. Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Base and spout with smooth interiors (reduces bacterial development).

Adjustable duty flush (pre-set at ~60 seconds every 24 hours after last use).

Flow rate limited to 4 lpm at 3 bar.

Shock-resistant infrared presence detection sensor.

Separate sensor for mounting on panels.

M3/8" solenoid valve with integrated filter.

Ø 60mm chrome-plated brass base.

Anti-blocking security.

Recommended installation height: 110 - 200mm above the basin surface.

Electronic tap suitable for use in healthcare facilities, retirement and care homes, hospitals and clinics.

Electronic tap suitable for people with reduced mobility.

30-year warranty.

Two shut-off options:

- standard mode: timed flow with automatic shut-off.
- ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.

Thermal shocks are possible.

Mount the sensor beside the tap in the ON/OFF mode.

TECHNICAL CHARACTERISTICS

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Connector	3/8"
Technology	Wall-mounted electronic tap
Depth	190mm
Length	129mm
Spout length	188mm
Flow rate	4 lpm at 3 bar
Finish	Chrome-plated brass

ADVANTAGES



Automatic duty flush limits bacterial development




Hygiene: spout can be removed and descaled inside



Hygiene: smooth interior reduces bacteria



No manual contact: infrared sensor



DELABIE

Norms	ACS (E ST
Warranty	30 g
Repairability	50g REPARABUTY

© DELABIE https://www.delabie.com