

# SECURITHERM EP pressure-balancing basin mixer

Ref. 2446EPS

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



## DESCRIPTION







**SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EPS**

Wall-mounted SECURITHERM pressure balancing (EP) basin mixer.  
 Wall-mounted mixer with flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.  
 Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa).  
 Stable temperature regardless of pressure and flow rate variations in the system.  
 Securitouch thermal insulation prevents burns.  
 Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.  
 Body and spout with smooth interiors and low water volume (reduces bacterial development).  
 Flow rate regulated at 5 lpm.  
 Chrome-plated brass body.  
 Sculptured control lever.  
 Mixer supplied with offset standard connectors M1/2" M3/4".  
 Recommended installation height: 110 - 200mm above the basin surface.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EPS**

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms	   
Warranty	
Repairability	

## ADVANTAGES



HW flow rate reduced if CW fails



Securitouch thermal insulation prevents burns



EP: prevention of pressure variations



Hygiene: smooth interior reduces bacteria

