

SECURITHERM EP pressure-balancing basin mixer

Ref. 2446EPS

Wall-mounted mixer with swivelling spout L. 150mm, sculptured lever



DESCRIPTION







SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EPS

Wall-mounted SECURITHERM pressure balancing (EP) basin mixer.
 Wall-mounted mixer with flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa).
 Stable temperature regardless of pressure and flow rate variations in the system.
 Securitouch thermal insulation prevents burns.
 Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume (reduces bacterial development).
 Flow rate regulated at 5 lpm.
 Chrome-plated brass body.
 Sculptured control lever.
 Mixer supplied with offset standard connectors M1/2" M3/4".
 Recommended installation height: 110 - 200mm above the basin surface.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446EPS

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms	   
Warranty	
Repairability	

ADVANTAGES



HW flow rate reduced if CW fails



Securitouch thermal insulation prevents burns



EP: prevention of pressure variations



Hygiene: smooth interior reduces bacteria

