SECURITHERM EP pressure-balancing basin mixer

Ref. 2446LEPS

Wall-mounted mixer with swivelling spout L. 150, Hygiene lever L. 150

DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446LEPS

Wall-mounted SECURITHERM Pressure Balancing (EP) basin mixer.
Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa).
Securitouch thermal insulation prevents burns.
Flat, swivelling under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL terminal filter.
Ø 40mm pressure-balancing ceramic cartridge and pre-set maximum temperature limiter.
Body and spout with smooth interiors and low water volume (reduces niches where bacteria can develop).
Flow rate regulated at 5 lpm.
Chrome-plated brass body.
Hygiene control lever L. 150mm.
Supplied with standard connectors M1/2" M3/4".
30-year warranty.

ADVANTAGES

- HW flow rate reduced if CW fails
- Securitouch thermal insulation prevents burns
- EP: prevention of pressure variations
- Body/spout with smooth interior reduces bacteria

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446LEPS

Connector	M1/2"
Technology	SECURITHERM EP, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	41°C
Finish	Chrome-plated brass
Norms	ACS, BELGAQUA, WRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY