


TEMPOMATIC direct flush valve

Ref. 463547

Electronic mains supply - sea water compatible



DESCRIPTION

TEMPOMATIC direct flush valve - Ref. 463547

Recessed electronic direct flush valve:

Mains supply with 1" solenoid valve.

230/12V transformer.

IP65 electronic housing unit.

Housing recessed behind a satin finish stainless steel plate 220 x 170mm.

Shock-resistant infrared presence detection sensor.

Voluntary activation (when hand is detected ~10cm in front of the sensor) or automatic flush when the user leaves.

Time flow ~7 seconds can be adjusted from 3 - 12 seconds.

Detection distance, flow rate and flush volume can be adjusted.

Sea water compatible.

Base flow rate: 1 L/sec.

Suitable for rimless WC pans.

30-year warranty.

This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMATIC direct flush valve - Ref. 463547

Supply	Mains supply 230/12V
Connector	1"
Technology	Electronic
Height	220mm
Width	170mm
Finish	Satin finish stainless steel
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



Direct flush: no water stagnation



Voluntary or automatic flush



Recessed installation

