

TEMPOMATIC WC direct flush valve

Ref. 463030HK

Electronic mains supply - sea water compatible







DESCRIPTION

TEMPOMATIC WC direct flush valve - Ref. 463030HK

Flush system without cistern: directly connected to pipework.
 Mains supply with 1" solenoid valve.
 230/12V transformer.
 IP65 electronic housing unit.
 For cross wall installation on walls ≤ 30 mm.
 Shock-resistant infrared presence detection sensor.
 Voluntary activation (when hand is detected ~ 10 cm in front of the sensor) or automatic flush when the user leaves.
 Time flow ~ 7 seconds can be adjusted from 3 - 12 seconds.
 Detection distance, flow rate and flush volume can be adjusted.
 Connection washer $\varnothing 32/55$ mm.
 Wall plate flush to the wall.
 Threaded rod can be cut to size.
 Base flow rate: 1 L/sec.
 Suitable for rimless WC pans.
 Sea water compatible.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC WC direct flush valve - Ref. 463030HK

Supply	Mains supply 230/12V
Connector	1"
Technology	Electronic
Length	30mm
Norms	 
Warranty	
Repairability	

ADVANTAGES



Total hygiene: no manual contact



No cistern: no water stagnation



Voluntary or automatic flush



Cross wall installation

