

# Mechanical sink or trough mixer

Ref. 2870T3

Single hole, single control tall mixer with ceramic cartridge

## DESCRIPTION

**Mechanical sink or trough mixer - Ref. 2870T3**

Deck-mounted mechanical sink mixer.  
Single hole, single control mixer with high, swivelling spout H. 320mm.  
Mixer supplied with 2 removable stainless steel spouts.  
Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.  
Body and spout with smooth interiors (reduced bacterial development).  
Thermal shocks are possible without removing the control lever or shutting off the cold water.  
Flow rate limited to 9 lpm at 3 bar.  
Touch-free control via the Hygiene lever L. 185mm.  
Body and base in chrome plated brass.  
PEX flexibles F3/8".  
Fixing reinforced by 2 stainless steel rods.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Mixer suitable for people with reduced mobility.  
Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical sink or trough mixer - Ref. 2870T3**

|                     |                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------|
| Connector           | F3/8"                                                                                   |
| Technology          | BIOCLIP mixer                                                                           |
| Drop height         | 320mm                                                                                   |
| Spout length        | 185mm                                                                                   |
| Flow rate           | 9 lpm at 3 bar                                                                          |
| Temperature limiter | Yes                                                                                     |
| Finish              | Chrome-plated brass                                                                     |
| Norms               | ACS  |
| Warranty            |      |
| Repairability       |      |



## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Hygiene: removable spout for internal cleaning



Flow rate limited to 9 lpm



Hygiene control lever requires no manual contact

