DELABIE

KOMPACT TC washbasin and floor-standing WC combination

Ref. 166600

Polished satin 304 stainless steel, cross wall - floor mount WC on RHS

DESCRIPTION

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

Combination unit: washbasin and floor-standing WC pan on right sidewith recessed toilet roll holder. Service duct installation (through-the-wall). Bacteriostatic 304 stainless steel. Polished satin finish. Stainless steel unit thickness: 2mm. Rounded corners and edges for improved safety. Smooth surface for easy cleaning. Suitable for prisons, police stations, etc. WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects. Washbasin equipped with time flow tap: stainless steel tamperproofpushbutton and anti-blocking system, 7 second time flow, M1/2". WC equipped with time flow flush valve, 7 second time flow, M3/4". Water inlet: washbasin M1/2", WC M3/4". Recessed horizontal water outlet: Ø 100mm 200mm threaded rod can be cut to size (other lengths available on demand). Weight: 30kg. [Formerly ref: 0616130006]

TECHNICAL CHARACTERISTICS

KOMPACT TC washbasin and floor-standing WC combination - Ref. 166600

| Height | 1000mm |
|-----------|------------------------------------|
| Length | 615mm |
| Width | 725mm |
| Thickness | 2mm |
| Finish | 304 polished satin stainless steel |
| Norms | ACS |
| Warranty | 30 M |



ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

