

# SECURITHERM shower panel

Ref. 792330

Thermostatic time flow dual control






## DESCRIPTION

**SECURITHERM shower panel - Ref. 792330**

SECURITHERM dual control thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With concealed inlet via flexibles, M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.  
2x ~30 second time flow valves to control fixed ROUND shower head and handset on flexible hose.  
Concealed fixings.  
Filters and non-return valves.  
Time flow shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792330**

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	   
Warranty	



## ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Aluminium body, brass controls

