## **SECURITHERM** shower panel

Ref. 792330

Thermostatic time flow dual control



## **ADVANTAGES**



Thermostatic temperature regulation



Immediate shut-off if cold water



80% water savings



Aluminium body, brass controls

## **DESCRIPTION**

SECURITHERM shower panel - Ref. 792330

SECURITHERM dual control thermostatic time flow shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation. With concealed inlet via flexibles,  $M_2^{\prime\prime}$ ".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Soft-touch operation.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.

2x ~30 second time flow valves to control fixed ROUND shower head and handset on flexible hose.

Concealed fixings.

Filters and non-return valves.

Time flow shower panel suitable for people with reduced mobility. 30-year warranty.

## TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792330

Connector	M½"
Technology	Time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS STF 😰 🔡
Warranty	30 g

