

SECURITHERM time flow shower panel

Ref. 792324

Time flow thermostatic and mechanical dual control




DESCRIPTION

SECURITHERM time flow shower panel - Ref. 792324

Thermostatic dual control shower panel:
Large satin stainless steel shower panel for wall mounted, exposed installation.
With top inlet via in-line stopcocks, M $\frac{1}{2}$ ".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
Handset with removable flexible via push-fit rapid STOP connector, wall support supplied.
~30 second time flow valve with soft-touch operation to control fixed ROUND shower head
1/4 turn non-time flow valve to control handset with flexible hose.
Thermal shocks are possible.
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 792324

Connector	M $\frac{1}{2}$ "
Technology	Non-time flow and time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  Fixed or handheld shower head
-  Stainless steel body, brass controls

